

FREE PROJECT SHEET GOOD VIBRATIONS QUILT | SIZE 531/2" x 691/2"



DESIGN ELIZABETH OLWEN

TECHNICAL EDITOR LINDA SPIRIDON

GOOD VIBRATIONS QUILT FEATURING GOOD VIBRATIONS BY ELIZABETH OLWEN

Fat quarters of each: Memory Lane, Groovescape, Flowerfield, Sunpatch, Polkadot Haze, Dashikiripple, Landline, Afterglow

23/4 yards Background

1/2 yard Flowerfield for Binding

41/3 yards Backing

Note: All possible care has been taken to assure the accuracy of this pattern. We are not responsible for printing errors or the manner in which individual work varies. Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.

CUTTING DIRECTIONS

Cutting dimensions include
1/4" seam allowances.

From each Fat Quarter:

4-6" x 6" squares (32 total)

4-2" x 6" rectangles (32 total)

4- 1½" x 6" rectangles (32 total)

From Background Fabric:

5-6" x WOF strips subcut into:

• 64- 1½" x 6" strips

• 24- 3½" x 6" strips

5-6" x WOF strips subcut into:

• Strip #1: 3-6" x 10½"

1-6" x 8"

• *Strip* #2: 1-6" x 10½"

2-6" x 8½"

1-6" x 8"

• Strip #3: 2-6" x 13 ½"

1-6" x 121/2"

• Strip #4: 2-6" x 13"

1-6" x 121/2"

DIAGRAMS

• Strip #5: 2-6" x 7½"

17-1½" x WOF strips (sashing) *subcut into*:

• 9- 1½" x 69½" strips

fig 1a fig 1b fig 1c fig 1d fig 1e

ASSEMBLY DIRECTIONS

BLOCK ASSEMBLY

- 1. Sew a $1\frac{1}{2}$ " x 6" background strip to the bottom of a 6" x 6" print fabric square. [fig 1a] Note direction of the print.
- 2. Use the same print fabric in Step 1, sew 2" x 6" print strip to the bottom of the background strip from step 1. [fig 1b]
- 3. Sew another $1\frac{1}{2}$ " x 6" background strip to the print strip from step 2. [fig 1c]
- 4. Sew the 1½" x 6" print strip of the same fabric to the bottom of the background strip in step 3 to complete the block. [fig 1d] Block should measure 6" x 10½". [fig 1e] Make 4 blocks from each fat quarter. 32 Total. Press all seams one direction.

ASSEMBLING THE QUILT

- 5. Refer to **QUILT DIAGRAM** for block placement as this quilt is pieced in vertical rows.
- 6. Vertical row 1, sew 6" x $8\frac{1}{2}$ " background piece to the top of the first block.
- 7. Sew 3½" x 6" background strips between the 3 remaining blocks in row 1.
- 8. Add 6" x $12\frac{1}{2}$ " background rectangle to the bottom block to complete row 1.
- 9. Following the **QUILT DIAGRAM**, continue to add 3½" x 6" background strips between the first 3 blocks in each row. Complete rows by adding the top and bottom background rectangles. Note these rectangle measurements vary for each vertical row.
- 10. Sew $1\frac{1}{2}$ " sashing strips end to end to equal vertical length of quilt (approximately $69\frac{1}{2}$ "). Make 9.
- 11. Pin sashing strip to the right side of each row and sew in place. Press toward strip.
- 12. Sew a sashing strip to the left side of row one.
- 13. Sew all rows together to complete the quilt top.
- 14. Layer backing, batting and quilt top.
- 15. Baste, quilt, and bind.

